

Pieter-Jan Van Bockstal¹, Joris Lammens¹, Jos Corver¹, Jan Van Hauwermeiren¹, Thomas De Beer¹
¹RheaVita, IIC UGent, Technologiepark Zwijnaarde 3, 9052 Ghent, Belgium

IMPLEMENTATION OF PAT FOR REAL-TIME PRODUCT MONITORING AND CONTROL DURING CONTINUOUS FREEZE-DRYING

Continuous freeze-drying

- Spin freezing of vials; cooling via cold gas
- Infrared-assisted primary and secondary drying
- Thin product layer leads up to 40x shorter processing time
- Uniform drying conditions for EACH vial
- No scale-up issues (as opposed to batch freeze-drying)
- 100% quality control at unit dose level




Figure 1: Illustration of spin freezing - Vials rapidly rotated to create a thin frozen product layer spread over the entire vial wall




Figure 2: Illustration of closed feedback loop to control the freezing and drying process

Opportunity

- Optimized and customized cooling & drying for each product
- Direct control of product temperature at individual vial level
- Identical freezing & drying conditions for each vial
- Same quality from pre-clinical to production no scale-up issues
- Fast formulation and process development with limited material

Implementation & Demonstration

- Closed loop control system during freezing and drying:
 - In Single Vial Continuous Freeze-Dryer (SVU):
 - Product cycle development and optimization
 - Formulation screening
 - In Industrial Scale GMP Continuous Freeze-Dryer (GMP Flex):
 - Product temperature control during production facilitating real-time release
- In-line NIR spectroscopy for residual moisture monitoring during the secondary drying step



Figure 3: Single Vial Continuous Freeze-Dryer (SVU)




Figure 4: Illustration of controlled spin freezing




Figure 5: Illustration of controlled drying: Temperature and residual moisture profile



Figure 6: Spin freeze-dried end product

